



# LATEX<sup>®</sup>ITE

BRAND

**RECREATIONAL COATINGS**

## LATEXITE ACRYLIC COMBO COATING SYSTEM

### Description and Usage

Latex-ite Acrylic Color Combo is a non-fading, weather-proof, 100% acrylic coating for use on plant mix asphalt, emulsified asphalt and suitable concrete surfaces. Latex-ite protects the underlying surface from weather and climactic conditions and is resistant to fuels, oils, alkalis and solvents. Made of acrylic resins, mineral fillers and colorfast pigments, the Latex-ite Acrylic Color System provides a tough, durable surface of uniform texture that remains flexible. Designed for use on tennis courts, basketball courts\*, recreational areas and various other usages, the finished texture is uniform throughout due to the aggregate being added at the factory to insure consistency throughout. Unlike other acrylic surfacing systems, each coat of Latex-ite Acrylic Color Combo is fully pigmented, resulting in richer, longer lasting, in depth color.

\*Three applications recommended in key areas.

### Color Range

Latex-ite Acrylic Color Combo is produced in eight standard colors: Dark Green, Light Green, Red, Dark Tan, Light Tan, Brown, Gray and Blue. Custom colors are available upon request.

### Mix Design

The Latex-ite Acrylic Color Combo is pre-mixed with 100 mesh silica sand. The material must be thoroughly mixed to insure a uniform consistency. The table below gives the amounts of water which may be added to the Latex-ite Acrylic Color Combo.

	Filler Coats	Finish Coat
Latex-ite Acrylic Color Combo	30 gallons	30 gallons
Potable Water	7-12 gallons	12-15 gallons
Note: Mix Design may need to be adjusted according to humidity, ambient temperatures and surface porosity.		

### Application Methods

Refer to the Court Surface Guidelines for surface preparation procedures. The Latex-ite Acrylic Color System is applied in three separate applications and is accomplished by use of a 24" to 48" long, flexible, 50 to 70 durometer rubber squeegee of good quality and in good condition. The first coat is a resurfacing coat, and the following 2 coats are fortified coats. The first coat will be applied in a perpendicular direction to the playing net. The second and third coat will be applied parallel with the playing net. Each application must thoroughly dehydrate before application of succeeding coat. The entire surface shall be checked for ridges and imperfections after each filler coat and scraped smooth and cleaned of all loose debris. Care must be taken to insure a smooth and uniform texture, free from ridges and tool marks, as the final coat is not to be scraped. An economy color system that can be applied to existing courts in good condition, would consist of two color coat applications.

## Coverage

Coverage will depend upon the porosity of the surface to which the Latex-ite Acrylic Color System is applied.

RESURFACING COAT = .05 GALLON PER SQUARE YARD  
FIRST FORTIFIED COAT = .06 GALLON PER SQUARE YARD  
SECOND FORTIFIED COAT = .055 GALLON PER SQUARE YARD

## Drying Time

30 to 90 minutes under optimum conditions. Humidity, surface temperature and ambient temperature will affect drying process.

## Limitations and Precautions

Latex-ite Acrylic Color Combo should not be applied when ambient temperature is below 50° F or when surface temperature is above 140° F. Do not apply when rain is imminent. Do not store in direct sunlight. Keep from freezing. Latex-ite Acrylic Color Combo should be allowed to cure for 24 hours before courts are opened for use.

## Limited Warranty and Disclaimer

Seller warrants to the original buyer only that the product is free from defects in material and workmanship. This warranty is not applicable if the product is used for purposes other than for which it was produced or if buyer does not follow all instructions and conditions for its use. This warranty is effective for the shorter of one year from date of purchase or until the sale or transfer of the product. If the product does not conform to this written warranty, buyer's remedy shall be limited to replacement of product or refund of purchase price. Buyer waives all other remedies and damages, including, but not limited to, any incidental and consequential damages, including property loss and loss of profits. **This warranty is expressly in lieu of all other warranties of merchantability and fitness. The buyer acknowledges that no other warranties or representations were made to him or relied upon by him.**