



TENNIS COURT  
**CRACKED?**

It doesn't have to be.



**ARMOR**  
TENNIS COURT CRACK REPAIR SYSTEM

# Tennis Court Cracking is Inevitable

The most common problem with asphalt tennis courts is cracking. Cracking is caused by asphalt's natural tendency to shrink as it weathers and ages. In addition, asphalt loses its flexibility and becomes more brittle over time. Since outdoor tennis courts are also exposed to temperature extremes that cause expansion and contraction, cracking is inevitable almost without exception.



## Others have tried

For decades, contractors have tried unsuccessfully to fix cracks with caulks, tar, rubber crack filler, foam backer rod, fiberglass membranes, or asphalt patches. These methods will not last one year. **When cracks are simply filled year after year**, not only does it look unsightly, but **it costs the owner more in the long run.**



## Tested in freeze/thaw climate

The most damaging conditions to tennis courts are extreme heat, freeze, and thaw. **The ARMOR® Crack Repair System has proven successful since its inception in 1993** under a variety of challenging climate conditions from Canada to the Caribbean.

## Our secret for long-lasting repairs

The ARMOR® Crack Repair System utilizes a knitted fabric that will expand as the crack widens. The secret to making this repair work is how it is purposely NOT bonded to the court in the vicinity of the crack, thereby allowing more of the fabric to absorb any movement or growth of the crack without the fabric tearing or delaminating from the surface. Thus, the reason why the ARMOR™ Crack Repair System works so well is that it effectively spreads the stress of the crack over a wide area of expandable fabric—**other brand name repair "systems" do not employ the ARMOR® slipsheet technology.**



Visit our website at [www.ArmorCrackRepair.com](http://www.ArmorCrackRepair.com).

## Repaired cracks will NOT reappear

Although your tennis court is technically still cracked, the filled cracks are hidden beneath our repairs and then painted to hide the repairs. ARMOR® will not prevent cracks from developing elsewhere on the court, or prevent cracks from growing in length out beyond the repair, **the ARMOR® Crack Repair System has successfully kept repaired structural cracks from reappearing on the surface of tennis courts since 1993.**

## ARMOR® repairs last.... and last

Most contractors simply install crack filler or put fiberglass fabric over the cracks. Almost without exception, both of these very common repair techniques will fail within one year, thus wasting both time and money. By using the ARMOR® Crack Repair System, your investment will last much longer than one season. In fact, **most ARMOR® repairs last more than 15 years.**

## Don't accept imitators

The success of ARMOR® has spawned some imitators. They claim to be "just as good," but their short histories cannot compare to decades of proven, worldwide achievements. In fact, ARMOR® has sold more crack repair than all of our competitors combined. Don't be fooled by deceiving marketing claims. These impostors can try to copy our product, but they cannot copy our success. **Insist on the original; insist on the best; insist on ARMOR®.**



## Successfully used around the world



ARMOR® Crack Repair System has been used to successfully repair millions of linear feet of cracks on tennis courts around the world and throughout the United States. Tennis court owners, contractors, and landscape architects worldwide are discovering every day the advantages of the ARMOR® Crack Repair System.



[ArmorCrackRepair.com](http://ArmorCrackRepair.com)

**1-877-99-ARMOR**

**View our short demo video on our homepage.**

**BEFORE**

**AFTER**



**Thousands of courts  
have ARMOR® installed.**

**Used on more than 4  
million feet of cracks.**

**Recommended by  
contractors worldwide.**

**Engineers specify  
ARMOR® by name.**

**Effective in sub-zero  
temperatures.**

**Proven successful  
since 1993.**

**ArmorCrackRepair.com  
877-99-ARMOR  
877-992-7667**

  
**ARMOR**  
**TENNIS COURT CRACK REPAIR SYSTEM**

5050 Industrial Road  
Farmingdale, NJ 07727  
© 2015 A.S.T.,LLC

# THE ARMOR® SYSTEM



A Patented Process for  
Long-Term Repairs to  
Asphalt Tennis Court Cracks



STEP 1: Fill cracks up to 4 inches wide



STEP 2: Sand flush to surface



STEP 3: Apply ARMOR® release tape



STEP 4: Apply liquid adhesive



STEP 5: Install narrow ARMOR® fabric



STEP 6: Install wide ARMOR® fabric



STEP 7: Install yellow ARMOR® mesh



STEP 8: Finished...ready to color coat!



Crack-Free Surface...Ready for Play!

5050 Industrial Road  
Farmingdale, NJ 07727  
© 2015 A.S.T.,LLC



**ARMOR**  
TENNIS COURT CRACK REPAIR SYSTEM

ArmorCrackRepair.com  
Toll Free 877-99-ARMOR  
877-992-7667